# **LED Luminaire**



## **Key Features:**

Main Body:

Clear Lens: Polycarbonate Gaskets:

Weight: 3.0kg

- Available in Green (Helidecks), Red (Obstruction) or White (general lighting) other colours also available.
- Customer can select constant light output or flashing upon installation.
- Conforms to ICAO annex 14 volume II and CAP437 for Helideck perimeter lighting and CAP168 for Obstruction lighting.
- LED technology will give a predicted working life of 10 years +.
- Utilises 6 off 1.2W LEDS.
- · Low power consumption.
- Easy installation and low maintenance.
- Rugged construction resistant to vibration.
- · Instant light output.
- 360° coverage.
- Independently photometrically tested.
- All units supplied with 3 cable entries.
- IP66 and IP67

- Optional wire guard available for extra protection.
- Can be supplied in traffic light or stop/start assemblies. Please contact sales office for further information.

Blackness Road Altens Industrial Estate Aberdeen **AB123LH** 

Tel: +44 (0) 1224 897755 Fax: +44 (0) 1224 877121 sales@unionsupplies.com www.unionsupplies.com

**Aberdeen** Baku

Dubai Houston



## **LED Luminaire**

### Protection:

IP66/67

## **Electrical Specifications:**

	Electrical Specification		
Lamp Options	Power consumption	Power factor	Power supply
6 x 1.2W LEDs	12W Max	0.95	100V - 254V 50/60Hz AC or 24V AC/DC

#### Installation:

Terminals: Up to 4mm<sup>2</sup> screwed terminals for live, neutral, earth and looping are provided. Internal and external earth is standard.

 $\textbf{Cable Entries: 3} \ x \ \text{M20, two fitted with stopper plug, other entries available on request.}$ 

Suspension: Via 4 external mounting points. Installation: Installation document supplied.

### Ordering Matrix:

Field Options
Product HDN103

Voltage H – 100-254V AC L – 24V AC/DC

Version\* G – Green LED'S R – Red LED'S W – White LED'S

Fittings 0 – No wire guard 1 – Wire guard fitted


Cable Entries 0 – M20 5 – M25

Other Options 00 – Red

00 – Ned 00 – White 02 – Green

\*Other colour options available

#### Dimensions:



#### Notes

- 1) Typical ordering reference HDN103HG0002.
- 2) Photometric Data available from the website or contact sales office.







